



# LED line PRIME LED strip 528 COB 24V 6500K 14W 30m



[[marketingIcon\_12\_kąt]]      [[marketingIcon\_13\_sideview]]      [[marketingIcon\_14\_spotless]]  
 [[marketingIcon\_19\_rgbw]]      [[marketingIcon\_20\_digital]]  
 [[marketingIcon\_21\_multiwhite]]      [[marketingIcon\_18\_twist]]  
 [[marketingIcon\_9\_RGB]]  
 [[marketingIcon\_16\_LED\_SAMSUNG]]  
 [[marketingIcon\_17\_ultra\_slim]]  
 [[marketingIcon\_136\_dim\_to\_warm\_strip]]  
 [[marketingIcon\_114\_warranty-3]]  
 [[marketingIcon\_115\_warranty-5]]      [[marketingIcon\_4\_3kroki]]  
 [[marketingIcon\_7\_HighCRI]]  
 [[marketingIcon\_15\_low\_voltage]]  
 [[marketingIcon\_8\_longerlifespan]]      [[marketingIcon\_6\_IES]]



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its esthetic appearance for many years.



The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Beam angle



LED type



Lifespan



LED quantity (1m)



LED quantity


Nazwa atrybutu	Wartość
Colour of the light	White
Correlated colour temperature	6000
Luminous efficacy	100
Energy efficiency class 2019/2015	F
Colour consistency in MacAdam ellipses	≤3
IP protection rating	20
Warranty (years)	5
Dimmable function	Yes
Survival factor	0.9
Minimum purchase quantity	30
Lifetime L70B50	50 000
Wattage (1m)	14
Luminous flux (1m)	1400
Current (1m)	0,58
Supply voltage range and voltage type	24V
Colour rendering index Ra	90
CRI colour rendering index	
Metres per roll	30
The lumen maintenance factor	96
Beam angle	180
LED type	COB
LED quantity	2640
Not dimmable	

Nazwa atrybutu	Wartość
Lifespan	
Number of on/off cycles	
Colour consistency in MacAdam ellipses	≤3
Ambient temperature suitable for operation	-30 ÷ 45
For indoor use	
IEC protection class	
Full box quantity	
Lamp's warm-up time to 60%	
Width	10
Height	2
Product weight with packaging (g)	
Master carton weight (kg)	
EPREL ID	
Date of first placement on the market	
Energy class	
Form of the product (EPREL)	Dotyczy 50cm taśmy
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No


Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	528
Cutting section	4,6
Type of adhesive tape	3M 300 LSE

Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	
Total luminous flux (EPREL)	700
On-mode power $P_{on}$ (EPREL)	7
Useful luminous flux $\Phi_{use}$ (EPREL)	700
Beam angle in degrees (EPREL)	180
Product code	200050

**Opakowanie jednostkowe**



**Opakowanie zbiorcze**



**Europaleta**

